

SAFETY DATA SHEET

Section 1 - Product and Company Identification

THE EMBALMERS' SUPPLY COMPANY

5 Colton Road

East Lyme, CT 06333

INFORMATION: 860-739-4200

EMERGENCY PHONE (24hr) CHEMTREC: 800-424-9300

www.embalmers.com - info@embalmers.com

Trade Name: Fluid Color Flesh Product Code: 22400

Product Type: Drainage Chemical

Revision Date: Mar-15

Section 2 - Hazards Identification

Appearance: Red Liquid Odor: Alcohol - Like

Emergency Overview: DANGER! Poison! May be fatal or cause blindness if swallowed. Vapor harmful. Harmful if swallowed, inhaled, or absorbed through skin. May cause respiratory and digestive tract

irritation. May cause kidney damage. May cause central nervous system effects. May cause cardiac disturbances. This contains material that has caused adverse reproductive and fetal

effects in animals.

Target Organs: Eyes, kidneys, heart, nervous system, optic nerve.

Potential Health Effects:

Inhalation: Methanol is toxic. Inhalation is the most common route of exposure. Causes CNS depression

with nausea, headache, vomiting, dizziness and incoordination.

Ethylene Glycol may cause respiratory tract irritation. Vapor inhalation generally not a problem unless heated or misted. May cause nausea, vomiting, dizziness and drowsiness.

Ingestion: Methanol may be fatal or cause blindness if swallowed. May cause gastrointestinal irritation

with nausea, vomiting and diarrhea. May cause central nervous system depression.

Ethylene Glycol may cause nausea and vomiting. Toxicity follows 3-stage progression: (1) involves central nervous system effecting including paralysis of eye muscles, convulsions, and coma. Metabolic acidosis and cerebral swelling may also occur. (2) involves cardiopulmonary system with symptoms of hypertension, rapid heart beat, and possible

cardiac failure. (3) involves sever kidney abnormalities including possible renal failure.

Skin: May cause skin irritation. Low hazard for usual industrial handling. Penetration may occur.

Eyes: Splashes may cause irritation, pain, eye damage.

Potential chronic health effects

Chronic Exposure: Repeated small exposures by any route can cause severe kidney problems. Brain damage

may also occur. Skin allergy can develop. May damage the developing fetus.

Aggravation of Pre-Existing Conditions:

Persons with pre-existing skin disorders, eye problems, or impaired liver, kidney, or

respiratory function may be more susceptible to the effects of Ethylene Glycol.

Section 3 – Composition/Information on Ingredients

<u>Ingredient Name:</u> <u>CAS number</u> <u>WT %</u>

Methanol (Methyl Alcohol) 67-56-1 8.1

Section 4 - First Aid Measures

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses. Do not allow victim to rub or keep eyes closed. Chemical burns must be treated promptly by a physician. Get medical

attention immediately.

Skin contact Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated

clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before

reuse.

Inhalation Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear.

Ingestion Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting

unless directed to do so by medical personnel. Never give anything by mouth to an

unconscious person. If vomiting occurs naturally, have victim lean forward.

Notes to physician Effects may be delayed. Ethanol may inhibit methanol metabolism.

Section 5 - Fire-fighting measures

General Information Ethanol may inhibit methanol metabolism. As in any fire, wear a self-contained breathing

apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapours may be heavier than air and may travel to a source of ignition and flash back. Vapours can spread along the ground and collect in low or confined areas. During a fire, irritation and highly toxic gases may be generated by thermal decomposition or combustion. Use a water spray to keep fire-exposed containers cool. Water may be ineffective. Material is

lighter than water and a fire may be spread by the use of water.

Extinguishing media

Suitable

For small fires use dry chemical, CO2, water spray, or alcohol resistant foam. For large fires,

use water spray, fog or alcohol-resistant foam.

Non-suitable Do NOT use straight streams of water.

Section 6 - Accidental Release Measures

General Information Use proper personal protective equipment as indicated in section 8

Spill/Leaks Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable

container. Remove all sources of ignition. Provide ventilation.

Section 7 – Handling & Storage

Handling Wash thoroughly after handling. Remover contaminated clothing and wash before reuse. Use

with adequate ventilation. Avoid contact with eyes, skin and clothing. Avoid ingestion and

200 ppm TWA;

260 mg/m3 TWA

inhalation.

Storage Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from

incompatible substances.

Section 8 – Exposure Control/Personal Protection

Ingredient Name: Occupational exposure limits

Methanol AGCIH TLV TWA NIOSH OSHA PEL STEL (15 mins)

200 ppm 200 ppm TWA; Skin – potential 260 mg.m3 TWA Significant contribution 6000 ppm IDLH

to overall exposure by

the cutaneous route.

OSHA Vacated PELs: Methanol: 200 ppm TWA; 260 mg.m3 TWA

Engineering Use adequate general or local exhaust to keep airborne concentrations below the permissible

exposure levels

Personal Protective Equipment

Eyes Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's

eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin Wear appropriate protective gloves to prevent skin exposure.

Clothing Respirators Wear appropriate protective clothing to prevent skin exposure.

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN149. Always use a NIOSH or European EN149 approved respirator when necessary.

Section 9 - Physical & Chemical Properties

Appearance (physical state, color, etc.) **Brown Liquid** Odor alcohol - liket

рΗ <7

Melting point/freezing point Freezes below 0° C **Boiling point** Boils below 100° C

Flash point 66.67 ° C (Tag Closed Cup)

No Data **Evaporation Rate**

Famability (solid/gas) Combustible liquid

Lower flammable limit 6.8% Upper flammable limit 36.0% Vapor pressure 92 mm Hg Vapor density 1.03 (Air = 1)Relative density 0.99

Water solubility Miscible Partition coeffficent: n-octanol/water water Auto ignition temperature No Data **Decomposition temperature** No Data ≥ Water Viscosity

Section 10 – Stability & Reactivity

Stability Stable under normal temperatures and pressures.

Conditions to avoid High temperatures, sources of ignition, incompatible materials.

Materials to avoid Oxidizing agents, reducing agents,

Hazardous Decomposition Products Thermal decomposition may produce carbon monoxide.

Section 11- Toxicological Information

Acute toxicity Ingredient Name:

Methanol LD50 Oral 7300 mg/kg Mouse 64000 ppm/4H LC50 Inhalation Rat LDLo Oral

Human 143 mg/kg LdLo Dermal Monkey 393 mg/kg

Other Toxicological Information

Carcinogenicity **Ingredient Name**

Methanol **ACGIH** Not Classified

> Not Classified IARC Not Classified NTP Not Classified **OSHA** Not Classified EU

Section 12 – Ecological Information

Environmental effects No known significant effects or critical hazards. Ethylene Glycol and Methanol are expected to biodegrade in soil and water very rapidly.

Aquatic Eco toxicity Ingredient Name

Methanol Fresh Water Acute EC 50 13,000 ,g/l/4/d Rainbow trout, donadson trout

Other adverse effects No known significant effects or critical hazards.

Section 13 - Disposal Considerations

Waste disposal Chemical waste generators must determine whether a discarded chemical is classified as a

hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste

regulations to ensure complete and accurate classification.

RCRA P-Series: None listed

RCRA U-Series: Methanol: waste number U154 (Ignitable waste).

Section 14 - Transportation Information

The data in this section is for information only and may not be specific to your package size or mode of transport. You will need to apply the appropriate regulation to properly classify your shipment.

International transport regulations

Regulatory UN/NA Proper shipping name Classes/*PG Reportable Information number Quantity (RQ)

CFR No Information available

TDG No Information available No Information available No Information available No Information available

*PG: Packing group

Section 15 - Regulatory Information

US regulations

TSCA CAS# 67-56-1 is listed on the TSCA inventory

SARA

Section 302 (RQ)

CAS# 67-56-1: 5000 lb final RQ; 2270 kg final RQ

Section 302 (TPQ)

None of the chemicals in this product have a TPQ

SARA Codes:

SARA 313 - Supplier Notification

This product contains Methanol (CAS# 67-56-1) which is subject to the reporting

requirements of Section 313 of SARA Title III and 40 CFR Part 373.

Clean Air Act: CAS# 67-56-1 is listed as a hazardous air Pollutant (HAP). This product does not contain any Class 1 Ozone depletors. This product does not contain any Class 2 Ozone

depletors.

Clean Water Act: None of the chemicals in this product are listed as Hazardous Substances under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. **OSHA:** None of the chemicals in this products are considered highly hazardous by OSHA.

State regulations CAS# 67-56-1 can be found on the following state right to know lists: California, New Jersey,

Pennsylvania, Minnesota, Massachusetts.

California No Significant Risk Level: None of the chemicals in this product are listed.

<u>Canada</u> CAS# 67-56-1 is listed on Canada's DSL List.

CAS# 67-56-1 is listed on the Canadian Ingredient Disclosure List

Hazard Symbols: XN Risk Phrases: R22 Harmful if swallowed.

Section 16 - Other Information

Prepared by
Date of issue
Date of printing
Version
Notice to reader

The Embalmers' Supply Company

13 March 2015

3

The information provided herein was believed by The Embalmers' Supply Company (ESCO) to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. All products supplied by ESCO are subject to ESCO's terms and conditions of sale. ESCO MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY ESCO, except that the product shall conform to ESCO's specifications. Nothing contained herein constitutes and offer for the sale of any product.